

WHAT IS CLAIMED IS:

- 1 1. A data transfer system comprising:
- 2 a plurality of first bus devices, at least one first bus
- 3 device being a first bus data supplying device capable of
- 4 supplying data, at least one first bus device being a first
- 5 bus data receiving device capable of receiving data and at
- 6 least one first bus device being a first bus master device
- 7 capable of requesting and controlling data transfer;
- 8 a first data bus connected to each of said plurality of
- 9 first bus devices and capable of transferring data from a
- 10 first bus data supplying device to a first bus data receiving
- 11 device under control of a first bus master device;
- 12 a plurality of second bus devices, at least one second
- 13 bus device being a second bus data capable of supplying device
- 14 capable of supplying data, at least one ~~second bus device~~
- 15 being a second bus data receiving device capable of receiving
- 16 data and at least one second bus device being a second bus
- 17 master device capable of requesting and controlling data
- 18 transfer;
- 19 a second data bus connected to each of said plurality of
- 20 second bus devices and capable of transferring data from a
- 21 second bus data supplying device to a second bus data
- 22 receiving device under control of a second bus master device;
- 23 a bus bridge connected to said first data bus and said
- 24 second data bus, said bus bridge capable of supplying data to
- 25 said first bus, receiving data from said first bus, supplying
- 26 data to said second bus, receiving data from said second bus,
- 27 not capable of controlling data transfer on said first bus and
- 28 capable of controlling data transfer on said second bus, said
- 29 bus bridge including

30 an address first-in-first-out memory having a
31 predetermined number of entries including an input
32 connected to said first bus and an output connected to
33 said second bus, and

34 a data first-in-first-out memory having said
35 predetermined number of entries including an input
36 connected to said first bus and an output connected to
37 said second bus.

1 2. The data transfer apparatus of claim 1, further
2 comprising:

3 a first bus arbiter connected to each of said at least
4 one first bus master device and said first bus, said first bus
5 arbiter granting control of data transfer on said first bus to
6 one and only one first bus master; and

7 a second bus arbiter connected to each of said at least
8 one second bus master device, said second bus and said bus
9 bridge, said second bus arbiter granting control of data
10 transfer on said first bus to one and only one of the set of
11 devices including each second bus master and said bus bridge.

1 3. The data transfer system of claim 1, wherein:

2 at least one first bus device being a first bus
3 supplying/receiving device capable of both supplying data to
4 said first bus and receiving data from said first bus.

1 4. The data transfer system of claim 3, wherein:

2 at least one first bus supplying/receiving device
3 consists of a central processing unit which is further capable
4 of controlling data transfer.

1 5. The data transfer system of claim 3, wherein:
2 at least one first bus supplying/receiving device
3 consists of a direct memory access unit which is further
4 capable of controlling data transfer.

1 6. The data transfer system of claim 3, wherein:
2 at least one first bus supplying/receiving device
3 consists of a memory which is not capable of controlling data
4 transfer.

1 7. The data transfer system of claim 3, wherein:
2 at least one first bus supplying/receiving device
3 consists of a central processing unit which is further capable
4 of controlling data transfer; and
5 said bus bridge further including at least one control
6 register accessible by said central processing unit, said bus
7 bridge setting a predetermined buffer full bit of said at
8 least one control register when said address
9 first-in-first-out memory and said data first-in-first-out
10 memory are full.

1 8. The data transfer system of claim 3, wherein:
2 at least one first bus supplying/receiving device
3 consists of a central processing unit which is further capable
4 of controlling data transfer; and
5 said bus bridge further operable to generate an interrupt
6 of said central processing unit when said address first-in-
7 first-out memory and said data first-in-first-out memory are
8 full.

1 9. The data transfer system of claim 8, wherein:
2 said bus bridge further including at least one control
3 register accessible by said central processing unit including
4 a buffer full interrupt enable bit, said bus bridge
5 selectively generating an interrupt of said central processing
6 unit when said address first-in-first-out memory and said data
7 first-in-first-out memory are full and said buffer full
8 interrupt enable bit has a predetermined digital state.

1 10. The data transfer system of claim 3, wherein:
2 at least one first bus supplying/receiving device
3 consists of a central processing unit which is further capable
4 of controlling data transfer; and
5 said bus bridge further including at least one control
6 register accessible by said central processing unit, said bus
7 bridge setting a predetermined buffer empty bit of said at
8 least one control register when said address first-in-first-
9 out memory and said data first-in-first-out memory are empty.

1 11. The data transfer system of claim 3, wherein:
2 at least one first bus supplying/receiving device
3 consists of a central processing unit which is further capable
4 of controlling data transfer; and
5 said bus bridge further operable to generate an interrupt
6 of said central processing unit when said address first-in-
7 first-out memory and said data first-in-first-out memory are
8 empty.

1 12. The data transfer system of claim 11, wherein:
2 said bus bridge further including at least one control
3 register accessible by said central processing unit including

4 a buffer full interrupt enable bit, said bus bridge
5 selectively generating an interrupt of said central processing
6 unit when said address first-in-first-out memory and said data
7 first-in-first-out memory are full and said buffer full
8 interrupt enable bit has a predetermined digital state.

1 13. The data transfer system of claim 3, wherein:
2 at least one first bus supplying/receiving device
3 consists of a central processing unit which is further capable
4 of controlling data transfer; and
5 said bus bridge further including at least one control
6 register accessible by said central processing unit, said bus
7 bridge setting a predetermined buffer full bit of said at
8 least one control register when an entry in said address
9 first-in-first-out memory and said data first-in-first-out
10 memory has been overwritten.

1 14. The data transfer system of claim 3, wherein:
2 at least one first bus supplying/receiving device
3 consists of a central processing unit which is further capable
4 of controlling data transfer; and
5 said bus bridge further operable to generate an interrupt
6 of said central processing unit when an entry in said address
7 first-in-first-out memory and said data first-in-first-out
8 memory has been overwritten.

1 15. The data transfer system of claim 14, wherein:
2 said bus bridge further including at least one control
3 register accessible by said central processing unit including
4 a buffer full interrupt enable bit, said bus bridge
5 selectively generating an interrupt of said central processing

TI-30251

9/6/00

6 unit when an entry in said address first-in-first-out memory
7 and said data first-in-first-out memory has been overwritten
8 and said buffer full interrupt enable bit has a predetermined
9 digital state.

090237-084704
T04T80-4222660